

MATERIAL SAFETY DATA SHEET

**TORGINOL® TA-12 TORGLAZE**

**SECTION 1 - PRODUCT INFORMATION**

<b>PRODUCT NAME:</b>	TA-12 TORGLAZE	<b>DATE OF PREPARATION:</b>	1/6/2006
<b>PRODUCT TYPE:</b>	COATING	<b>PHYSICAL FORM:</b>	SOLVENT
<b>COMPANY ADDRESS:</b>	TORGINOL, INC. P O BOX 102 710 FOREST AVENUE SHEBOYGAN FALLS, WI 53085	<b>TELEPHONE:</b>	(800) 558-7596
		<b>EMERGENCY TELEPHONE:</b>	(800) 688-4005

**SECTION 2 - HAZARDOUS INGREDIENTS/COMPOSITION INFORMATION**

INGREDIENT:	% BY WGT	CAS NO.	ALLOWABLE EXPOSURE LEVEL		SARA 313	VP MM Hg @ 20 DEG.C	
			PPM	MG/CU.M.			
POLYURETHANE PREPOLYMER		TSRNMH2801	NONE ESTABLISHED				
XYLENE	45	1330-20-7	TLV-TWA	100	435	X	5
			TLV-STEL	150	655		
			OSHA-PEL	100	435		
			OSHA-STEL	150	655		
			LFL	1.0	UFL		
PROPYLENE GLYCOL METHYL ETHER ACETATE		108-65-6	NONE ESTABLISHED			2	
ETHYL BENZENE	10	100-41-4	TLV-TWA	100	435	X	1
			TLV-STEL	125	545		
			OSHA-PEL	100	435		
			OSHA-STEL	125	545		
			LFL	1.0	UFL		

LFL = LOWER FLAMMABILITY LIMIT PERCENT  
 UFL = UPPER FLAMMABILITY LIMIT PERCENT  
 SKIN = SKIN ABSORPTION MUST BE CONSIDERED AS A ROUTE OF EXPOSURE  
 C-CEILING = ALLOW. EXPOSURE LEVEL SHOULD NOT BE EXCEEDED FOR ANY TIME PERIOD.  
 MFR = MANUFACTURER RECOMMENDED EXPOSURE LIMIT  
 STEL = SHORT TERM EXPOSURE LIMIT  
 X-SARA 313 = CHEMICAL IS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF S.A.R.A. 40 CFR PART 37;

**SECTION 3 - HAZARDS IDENTIFICATION**

**H.M.I.S**

<b>HEALTH</b>	<b>3*</b>	THESE RATINGS SHOULD BE USED ONLY AS PART OF FULL IMPLEMENTED H.M.I.S PROGRAM
<b>FLAMMABILITY</b>	<b>3</b>	
<b>REACTIVITY</b>	<b>1</b>	

**EFFECTS OF SHORT TERM OVER EXPOSURE**

**SWALLOWING**

MAY BE FATAL IF SWALLOWED.  
 CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, AND VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL

**INHALATION**

WARNING: VAPOR AND SPRAY MIST HARMFUL. OVER EXPOSURE MAY CAUSE LUNG DAMAGE. MAY CAUSE LUNG IRRITATION AND ALLERGIC RESPIRATORY REACTION. EFFECTS MAY BE PERMANENT.  
 MAY CAUSE RESPIRATORY SENSITIZATION (POTENTIAL FOR ALLERGIC REACTION).  
 MAY CAUSE THROAT OR NOSE IRRITATION. HIGH CONCENTRATION MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHES, DIZZINESS, NAUSEA AND CONFUSION.

**EYE**

MAY CAUSE SEVERE EYE IRRITATION

**SKIN**

PRIMARY SKIN IRRITANT.  
 MAY CAUSE SKIN SENSITIZATION (ALLERGIC REACTION). MAY CAUSE SEVERE SKIN IRRITATION.

**EFFECTS OF REPEATED EXPOSURE**

OVEREXPOSURE TO XYLENE MAY CAUSE INJURY TO THE LIVER, KIDNEYS AND BLOOD.  
 REPEATED EXPOSURE TO DIISOCYANATES MAY RESULT IN SKIN AND RESPIRATORY SENSITIZATION IN SOME INDIVIDUALS. RESPIRATORY SENSITIVITY RESULTS IN ASTHMA-LIKE SYMPTOMS ON SUBSEQUENT EXPOSURE AT CONCENTRATIONS EVEN BELOW THE TLV.  
 REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

---

## SECTION 4 - FIRST AID MEASURES

---

<b>SWALLOWING</b>	OF SWALLOWED DO NOT INDUCE VOMITING. (NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON). CALL POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM, OR PHYSICIAN IMMEDIATELY.
<b>INHALATION</b>	REMOVE TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP WARM AND QUIET. GET MEDICAL ATTENTION IMMEDIATELY.
<b>EYE</b>	FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. CONTINUE FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY.
<b>SKIN</b>	REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP AND WATER. OBTAIN MEDICAL ATTENTION IF IRRITATION PERSISTS.
<b>NOTES TO PHYSICIAN</b>	ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

---

## SECTION 5 - FIRE FIGHTING MEASURES

---

**NFPA FLAMMABILITY CLASSIFICATION**                      **FLAMMABLE LIQUID - CLASS IC**

**FLASHPOINT**                      80 DEG.F,SFCC                      ( 27 DEG.C.)

### **EXTINGUISHING MEDIA:**

USE NFPA CLASS B FIRE EXTINGUISHERS (CARBON DIOXIDE, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) DESIGNED TO EXTINGUISH FLAMMABLE LIQUID FIRES. POLYMER FOAM IS DESIGNED FOR LARGE FIRES.

### **UNUSUAL FIRE AND EXPLOSION HAZARDS:**

DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

### **WARNING! FLAMMABLE**

### **SPECIAL FIRE FIGHTING PROCEDURES**

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

---

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

---

### **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

THE USE OF NIOSH/MSHA APPROVED, TC19C, AIR-SUPPLIED BREATHING APPARATUS MAY BE REQUIRED. CONSULT WITH A QUALIFIED OCCUPATIONAL HEALTH AND/OR SAFETY PROFESSIONAL.

RESORT TO SECTION 8 AND DON RESPIRATORS, EYE, HAND, AND BODY PROTECTION APPROPRIATE FOR THE SIZE OF THE SPILL AND THE EXPOSURE ENCOUNTERED. KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITION SOURCES (FLAMES, HOT SURFACES, AND SOURCES OF ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). DIKE AND CONTAIN SPILL WITH INERT MATERIAL (E.G SAND, EARTH). TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL, OR REMOVE WITH INERT ABSORBENT. USE ONLY NON-SPARKING TOOLS. PLACE ABSORBENT DIKING MATERIALS IN COVERED METAL CONTAINERS FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS, STREAMS, AND GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORBENT.

### **WASTE DISPOSAL**

DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

### **RCRA CLASSIFICATION**

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS A HAZARDOUS WASTE BASED ON IT'S IGNITABILITY CHARACTERISTICS, I.E HAS A FLASH POINT OF 140 deg. F. (60 deg. C) OR LESS. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

### **ENVIRONMENTAL HAZARDS**

NONE KNOWN

---

## SECTION 7 - HANDLING & STORAGE

---

### **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

AVOID CONTACT. REFER TO SECTION 8 FOR EXPOSURE CONTROL. DO NOT STORE ABOVE 115 deg. F (46 deg. C) STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

### **OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. AVOID SKIN CONTACT. THIS PRODUCT SHOULD NOT BE USED BY PERSONS WHO HAVE HAD CHRONIC (LONG TERM) BREATHING PROBLEMS OR REACTIONS TO ISOCYANATES. DO NOT BREATHE VAPOR, SPRAY, OR MIST. DO NOT GET IN EYES, SKIN, OR CLOTHING. WASH THOROUGHLY AFTER HANDLING. KEEP AWAY FROM HEAT, SPARKS,OR FLAMES. USE ONLY WITH ADEQUATE VENTILATION.

---

## SECTION 7 - HANDLING & STORAGE (CONT'D)

---

**OTHER PRECAUTIONS (CONT'D)**

WASH HANDS AND FACE THOROUGHLY BEFORE EATING OR DRINKING. EMPTY CONTAINERS MUST NOT BE WASHED AND RE-USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL.

**SECTION 8 - EXPOSURE CONTROLS****RESPIRATORY PROTECTION**

PROPER SELECTION OF RESPIRATORY DEPENDS ON MANY FACTORS INCLUDING DURATION/LEVEL OF EXPOSURE AND CONDITIONS OF USE. IN GENERAL EXPOSURE TO ORGANIC CHEMICALS SUCH AS THOSE CONTAINED IN THIS PRODUCT MAY NOT REQUIRE THE USE OF RESPIRATORY PROTECTION IF USED IN WELL VENTILATED AREAS. IN RESTRICTED VENTILATION AREAS A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. UNDER CERTAIN CONDITIONS, SUCH AS SPRAYING, A MECHANICAL PREFILTER MAY ALSO BE REQUIRED. IN CONFINED AREAS USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. IF THE TLV'S LISTED IN SECTION 2 ARE EXCEEDED USE A PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR WITH AN APPROPRIATE PROTECTION FACTOR. REFER TO OSHA 29 CFR 1910.134 "RESPIRATORY PROTECTION", AND "RESPIRATORY PROTECTION A MANUAL AND GUIDLEINE, AMERICAN INDUSTRIAL HYGIENE ASSOC."

**VENTILATION**

PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO KEEP CONCENTRATIONS OF HAZARDOUS INGREDIENTS LISTED IN SECTION 2 BELOW THE LOWEST EXPOSURE LIMIT STATED. REMOVE DECOMPOSITION PRODUCTS THAT ARE GENERATED WHEN WELDING, CUTTING, OR BRAZING OBJECTS COATED WITH THIS PRODUCT. REFER TO "INDUSTRIAL VENTILATION - A MANUAL OF RECOMMENDED PRACTICE" ACGIH

**HAND PROTECTION**

BUTYL RUBBER

NITRILE GLOVES

WEAR APPROPRIATE IMPERMEABLE GLOVES.

**EYE PROTECTION**

WEAR SAFETY GLASSES MEETING THE SPECIFICATIONS OF ANSI Z87.1 WHERE NO CONTACT WITH THE EYE IS ANTICIPATED. CHEMICAL SAFETY GOGGLES MEETING THE SPECIFICATIONS OF ANSI Z87.1 SHOULD BE WORN WHENEVER THERE IS A POSSIBILITY OF SPLASHING OR OTHER CONTACT WITH THE EYES.

**OTHER PROTECTIVE EQUIPMENT**

EYE WASH FACILITY, SAFETY SHOWER. AS REQUIRED TO PREVENT SKIN CONTACT.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING RANGE</b>	NOT APPLICABLE		
<b>VAPOR DENSITY</b>	HEAVIER THAN AIR		<b>% VOLATILE BY VOLUME</b> 67
<b>EVAPORATION RATE</b>	<b>VOC 4.86 lb/gal</b>	<b>LESS WATER&amp; NPRS*</b>	583 g/l LESS WATER CALCULATED
SLOWER THAN DIETHYL ETHER.			
<b>WEIGHT LB./GAL.</b>	<b>8.0</b>	<b>VOC 14.73 lb/gal</b>	<b>SOLIDS</b> 1768 g/l LESS WATER CALCULATED
SPECIFIC GRAVITY 1.0			

ALL PHYSICAL DATA DETERMINED AT 68 DEG. F. (20 DEG. C.) 760 mm Hg

\* NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS

**SECTION 10 - STABILITY**

**STABILITY:** NORMALLY STABLE

**CONDITIONS TO AVOID:**

AVOID EXCESSIVE HEAT (>115 deg. F (46 deg. C)) AND SOURCES OF IGNITION.

**INCOMPATIBILITY (MATERIALS TO AVOID):**

STRONG ACIDS OR ALKALINE MATERIALS

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:**

BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE. IN ADDITION, OXIDES OF NITROGEN MAY BE GENERATED. THE REACTION OF ISOCYANATES WITH WATER MAY PRODUCE CARBON DIOXIDE GAS WHICH MAY RESULT IN CONTAINER PRESSURIZATION.

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR

**CONDITIONS TO AVOID:** NONE KNOWN

---

**SECTION 11 - TOXICOLOGICAL INFORMATION & SECTION 12 - ECOLOGICAL INFORMATION**

---

NO DATA AVAILABLE

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

---

SEE SECTION 6

---

**SECTION 14 - TRANSPORT INFORMATION**

---

<b>ITEM:</b> TA-12 TORGLAZE	<b>DESC/SIZE:</b> TA-12 PAIL/40 LB			
<u>MODE</u>	<u>PROPER SHIPPING NAME</u>	<u>CLASS</u>	<u>I.D.#</u>	<u>PKG GRP.</u>
IATA (AIR)	LIMITED TO SMALL QUANTITIES ONLY CANNOT BE SHIPPED IN THIS CONFIGURATION NAERG: 127			
DOT (HM-181) (DOMESTIC SURFACE)	RQ, RESIN SOLUTION (XYLENE) NAERG: 127	3	UN1866	III
IMDG CODE (OCEAN)	RQ, RESIN SOLUTION (XYLENE)	3	UN1866	III

NOTE! THE ASSIGNMENT OF PROPER SHIPPING NAMES IS IN PART A FUNCTION OF THE SIZE OF THE PRODUCT CONTAINER AND THE TRANSPORT MODE. FOR EXAMPLE, THE PROPER SHIPPING NAME FOR A BULK CONTAINER CAN DIFFER SIGNIFICANTLY FROM THE PROPER SHIPPING NAME FOR THE SAME PRODUCT PACKAGED IN A NON-BULK CONTAINER. THIS CAN ALSO BE TRUE FOR PRODUCTS SHIPPED VIA DIFFERENT MODES OF TRANSPORTATION (i.e GROUND, AIR, OCEAN) . THE DESCRIPTIONS PROVIDED ABOVE ARE INTENDED TO PROVIDE SOME GUIDANCE. HOWEVER, THESE DESCRIPTIONS MAY NOT APPLY TO YOUR PACKAGE SIZE OR MODE OF SHIPMENT.

THE U.S CODE OF FEDERAL REGULATIONS, 49 CFR - TRANSPORTATION, REGULATIONS, AND THE POLICIES ESTABLISHED BY SOME TRANSPORTERS, REQUIRE THAT THE SHIPPER PROPERLY CLASSIFY AND ASSIGN A PROPER SHIPPING NAME, AND LABEL, MARK AND PACKAGE THE MATERIAL PROPERLY. THEREFORE, THE USER OF THIS INFORMATION IS CAUTIONED TO CONSULT WITH APPLICABLE REGULATIONS, AND WITH QUALIFIED ADVISORS PRIOR TO THE REPACKAGING AND/OR RESHIPMENT OF THIS OR ANY OTHER PRODUCT WHICH CONTAINS THIS PRODUCT.

---

**SECTION 15 - REGULATORY INFORMATION**

---

**ALL INGREDIENTS IN THIS PRODUCT ARE LISTED ON THE US TSCA INVENTORY.  
ALL INGREDIENTS IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCE LIST**

**WARNING:** THIS PRODUCT CONTAINS **ETHYL BENZENE**; A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>DETAIL INVENTORY LIST INFORMATION</u>
POLYURETHANE	TSRNMH2801	DSL
XYLENE	1330-20-7	TSCA (8a PAIR) DSL
PROPYLENE GLYCOL	108-65-6	TSCA (8a PAIR)
METHYL ETHER ACETATE		TSCA (8d) TSCA (8d term) DSL
ETHYL BENZENE	100-41-4	TSCA (4a) TSCA (8a PAIR) TSCA (8d) DSL

**DETAIL INVENTORY LIST DESCRIPTION**

TSCA /TOXIC SUBSTANCE CONTROL ACT

(4a) TSCA 4a

(8a PAIR) PRELIMINARY ASSESSMENT INFORMATION RULES

(8d) HEALTH AND SAFETY REPORTING RULES

(8d term) HEALTH AND SAFETY REPORTING RULES TERMINATION

DSL/CANADIAN DOMESTIC SUBSTANCE LIST