

4617 South Taylor Drive Sheboygan, WI 53081 | USA Toll-Free 1-800-558-7596 (920) 694-4800 | (920) 694-4801 Fax service@torginol.com | www.torginol.com

Product Data Sheet



Polymer ColorFlakes™

Decorative Polymer Color Chips/Flakes

For use in Resinous Performance Floor Coating Systems

DESCRIPTION

Product Name:

Decorative Vinyl Color Chips/Flakes Trade Name: *ColorFlakes* ™

Manufacturer:

Torginol, Inc.
4617 South Taylor Drive
Sheboygan, WI 53081 USA
(800) 558-7596 toll-free
(920) 694-4800 telephone
(920) 694-4801 facsimile
www.torginol.com
service@torginol.com

Torginol ColorFlakes ™, also known as color chips, flake or fleck are composed of water-based resin materials, inorganic minerals, additives and various pigments. This unique product is integrally pigmented, brilliantly colored, random in shape, sized within a standardized range and custom blended with infinite options to achieve optimal appearance and texture qualities with a resin-based flooring or wall-coating system.

ColorFlakes™ Advantages:

- Custom design to match any décor
- Over 150 color-styles "in-stock"
- Non-flammable
- Water-based chemistry
- Optimal flexibility & strength
- Colorfast, UV stable pigments
- Forgiving application
- Fast turnaround times
- Custom color-matching available
- Six standard sizing options
- Infinite custom-blending options
- Custom blend-matching expertise
- Lab tested resin compatibility
- Suitable in many environments
- Custom packaging & label options
- No minimum order quantities
- Diligent quality control program
- Hide sub-surface imperfections

CHARACTERISTICS

Color:

Spectrophotometer ASTM E1866 $\Delta E \le 1.0$ Pass

Dry Film Thickness:

Micrometer ASTM D1005
Mils Dry 4 - 5 mils

Shape:

Visual Evaluation

Random Pass

Odor:

Olfactory Evaluation ASTM D1296
Odorless Pass

Surface Texture:

Visual Evaluation

Smooth Pass

Metamerism:

Visual Evaluation ASTM D4086 Nonmetameric Pass

Sheen:

60° Gloss Meter ASTM D523 <15 units Pass

Dry Film Flexibility:


Mandrel Bend Test ASTM F137*
Interior Angle ≤ 110° Pass

Hiding Power:

Visual Evaluation ASTM D6762 Opacity > 98% Pass

(except color C2250)

Size Distribution:



SIZING & BLENDING

Sizing Options:



Original (~1")



1/2"



1/4"



1/8"



1/16"



1/32"

Custom Blending:

Use ColorFlakes[™] to coordinate your floors and walls with any décor. Our extensive line of ColorFlakes[™] gives you the ability to custom design blends to match any colorscheme. Either choose from one of our signature blend designs or creatively mix and match colors to develop a unique color array that best fits your project. *Call 1-800-558-7596 for more information and to request samples...*



Polymer ColorFlakes™

Decorative Polymer Color Chips/Flakes



COLOR INDEX

OOLOR INDLX			
(Sorted by Item	Number)		
•	,		
Standard Colors			
F1000 (Adobe Beige)	F9805 (Carrot Cake)		
F1020 (Amethyst)	F9806 (Flesh)		
F1040 (Autumn Brown)	F9902 (Black Iron Oxide)		
F1045 (Beige)	F9903 (Online)		
F1050 (Black)	F9904 (Dark Grey)		
	ECOOOF (Heaven)		
F055 (Brick Red)	FC9905 (Heaven)		
F1060 (Brown)	F9907 (Blue Ox)		
F1070 (Burgundy)	F9908 (Canary Yellow)		
F1080 (Canyon Red)	F9909 (Sugar Cookie)		
F1090 (Charcoal)	F9910 (Buttermilk)		
F1100 (Cocoa Brown)	F9911 (Fossil)		
F1120 (Crest Green)	F9912 (Toast)		
F1130 (Dark Blue)	F9916 (Favre)		
F1140 (Delray Blue)	F9920 (Cherry Bomb)		
F1160 (Dove Gray)	F9951 (Plum)		
F1200 (Dusk Blue)	F9952 (Aquamarine)		
F1320 (Fawn)	F9953 (Honeydew)		
F1360 (Forest Green)	F9954 (Caramel)		
F1400 (Gold)	F9955 (Battleship Gray)		
F1410 (Granite)	F9956 (Khaki)		
F1415 (Graphite)	F9957 (Taupe)		
F1420 (Hunter Green)	F9958 (Alpaca White)		
F1425 (Ivory)	F9959 (Antique White)		
F1430 (Jasper)	F9960 (Navajo Beige)		
F1480 (Medium Gray)	F9961 (Functional Gray)		
F1520 (Milkweed)	E0062 (Intercem)		
	F9962 (Jetstream)		
F1560 (Mint Green)	F9963 (Cobalt Blue)		
F1570 (Mustard)	F9964 (Sky Blue)		
F1600 (Olive)	F9965 (Lavender)		
F1640 (Patio Red)	F9966 (Morning Fog)		
F1680 (Peach)	F9967 (Royal Blue)		
F1720 (Powder Blue)	F9968 (Steel Blue)		
F1760 (Rose)	F9969 (Navy)		
F1770 (Salmon)	F9970 (Moss)		
F1780 (Scone)	F9971 (Peppermint)		
F1785 (Tan)	F9972 (Moody Blue)		
F1790 (True Blue)	F9973 (Coppertone)		
F1800 (Whisper Gray)	F9974 (Brilliant Blue)		
F1820 (White)	F007F (Drilliant Blue)		
	F9975 (Raisin)		
F2160 (Orange)	F9977 (Daiquiri)		
F2200 (Primary Yellow)	F9978 (Tomato)		
F2240 (Red)	F9979 (Squash)		
F2250 (Semi-Transparent White)	F9981 (Potter)		
F5051 (Afterglow)	F9982 (Gravy)		
F5052 (Chocolate)	F9983 (Hypnotic)		
F5101 (Seaspray)	F9984 (Sonic)		
F5102 (Lime)	F9985 (Susie-Q)		
F5103 (Sorbet)	F9986 (Eggshell)		
F5104 (African Violet)	F9987 (Stone)		
F5114 (Ebony)			
	F9988 (Baby Blue)		
F5115 (Putty)	F9989 (Purple Haze)		
F5116 (Wigwam)	F9990 (Slime)		
F5117 (Acorn)	F9991 (Gardenview)		
F5118 (Fireweed)	F9992 (Cosmo)		
F5252 (Cement)	F9993 (Grape)		
F5301 (Cornmeal)	F9994 (Sand Dune)		
F5302 (Cardboard)	F9995 (Berry)		
F5303 (Cappuccino)	F9996 (Redwood)		
F5304 (Mud)			
F5305 (Tabu)	Marble / Stone		
F5306 (Porpoise)	F9303 (Pumice)		
F5307 (Camelback)	F9304 (Obsidian)		
	F9305 (Garnet)		
F5910 (JD Green)	E0307 (Schiet)		

F9307 (Schist) F9309 (Basalt) F911 (Dolorite)

F5920 (Cyberspace)

F6602 (Latte) F6604 (Primary Blue)

F6606 (Neutral Gray) F6607 (Clay)

F6612 (Creamy Orange) F6613 (Sage)

F6616 (Lemon Yellow)

F6622 (Sunrise Yellow)

F6721 (Lipstick Red)

F6723 (Camo Green)

F7551 (Terra Cotta) F9800 (Sommelier)

F6804 (Gladiola)

F9801 (Dolphin)

F6617 (Teal) F6621 (Stormy Blue)

F6609 (Burnt Red) F6611 (Evergreen)

F6614 (Cream)

F6615 (Pumpkin)

F5935 (Rustic Red)

F6601 (Buff)

F3020 (V.C. Ewa Green) F3040 (V.C. Kona Beige) F3080 (V.C. Lanai Gray) F3100 (V.C. Maui Blue) F3120 (V.C. Pali Brown) F3160 (V.C. Rose)

Photoluminescent F9110 - Blue Glow F9120 - Green Glow

Fluorescent Black Light Sensitive F4000 (Blaze Orange) F4040 (Chartreuse) F4080 (Hot Pink) F4120 (Rocket Red) F4160 (Signal Green) F4180 (Horizon Blue)

APPLICATION

Floor Application Coverage Rates

Flake Size	<u>Full</u>	<u>Partial</u>	
Original (~1")	8-10	25-200	ft²/lb.
1/2"	7-9	25-200	ft²/lb.
1/4"	5-7	25-200	ft²/lb.
1/8"	4-6	25-200	ft²/lb.
1/16"	3-5	25-200	ft²/lb.
1/32"	2-4	25-200	ft²/lb.

*Coverage rates vary depending on customer preferences and application techniques. Torginol does not guarantee exact coverage rates.

Floor Application Methods

Hand Broadcasting:




Pneumatic Hopper-Blower Gun:



TYPICAL SYSTEM

(approximate dry film thickness: 15 - 30 mils)



For best results, 10-15 mils of clear top-coating is recommended to fully encapsulate ColorFlakes™ and provide a durable wearing surface.

SYSTEM COMPATIBILITY

Lab tested resin chemical compatibility:

- Epoxy
- MMA
- Polyurethane
- Polyaspartic
- Polyurea
- · And others...

Various Polymers

Note:

In 40+ years of manufacturing ColorFlakes™, there are no known resin incompatibilities. However. Torginol recommends unknown resin compatibility testing prior to use.

PRODUCT LIMITATIONS

- ColorFlakes[™] are random in shape due to our manufacturing process.
- · Although the colorfast pigments in the ColorFlakes™ are UV stable, the specifications for the UV stability and environmental durability of your coating system will determine outdoor suitability.
- Due to inherent product characteristics, a small amount of finer particles will be present within each box.
- Do NOT apply ColorFlakes™ in rain.

STORAGE

Store ColorFlakes™ in an air tight poly-bag in a dry environment at room temp. to avoid moisture, humidity and product degradation.

RECOMMENDED USES











Banquet Halls Bars, Pubs & Taverns Basements Bathrooms Bowling Alleys Butcher Shops Cafeterias Churches Clean Rooms Commercial Kitchens Dog Kennels Garage Floors Greenhouses **Grocery Stores** Hallways Hospitals Industrial Hallways Laboratories Laundromats Locker Rooms Lunch Rooms Night Clubs Offices Pet Stores Pharmaceutical Plants Public Municipalities Restaurants Restrooms Retail Stores Show Rooms Stadium Hallways And more...

Aircraft Hangers